

Polaris Material Safety Data Sheet

Polaris Sales Inc.
2100 Highway 55
Medina, MN 55340

Emergency: 800-424-9300
Information: 763-542-0500

SECTION 1 CHEMICAL PRODUCT IDENTIFICATION

Product: Polaris VES/ GOLD PLUS
CAS Registry Number: Mixture
Synonyms: Not applicable.
MSDS Number: 10309
Product Type: 2 Cycle Engine Lubricant
Preparation/Revision Date: 8/4/2010

SECTION 2 HAZARDOUS COMPOSITION INFORMATION

INGREDIENTS	CAS #	%	ACGIH TWA	OSHA PEL	ACGIH STEL	SKIN
Light hydrotreated distillate	64742-47-8	0-10	100 ppm	500 ppm	500 ppm	NO
Severely refined petroleum distillates	Mixture	45-55	5 mg/m ³ (oil mist)	5 mg/m ³ (oil mist)	10 mg/m ³ (oil mist)	NO
Proprietary additives	Mixture	Balance	Not Available	Not Available	Not Available	NO

SECTION 3 HAZARDOUS IDENTIFICATION

WARNING: - MAY CAUSE EYE IRRITATION
- HARMFUL IF SWALLOWED
- COMBUSTIBLE

Eye contact: May cause slight irritation.

Skin contact: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

Inhalation: Central nervous system may be affected. Symptoms include headache, dizziness, loss of appetite, weakness and/or loss of coordination.

Ingestion: Material is expected to be non-toxic to internal organs if swallowed. However, due to product's low viscosity, aspiration may occur during swallowing or vomiting. Aspiration may result in chemical pneumonitis.

Other: Not determined.

SECTION 4 FIRST AID MEASURES

Eye contact: Flush eyes with running water for 15 minutes, holding eyelids open to expose surface of eye. Contact physician.

Skin contact: Remove contaminated clothing. Wash skin with soap and water. Get medical attention if irritation develops or persists.

Inhalation: Remove to fresh air at once. Apply artificial respiration if necessary, contact physician immediately.

Ingestion: Do not induce vomiting. Contact a physician immediately.

Other: Not determined.

SECTION 5 FIRE FIGHTING MEASURES

Polaris Material Safety Data Sheet

Flash point:	>200°F ASTM D-92
Flammable limits:	Not determined.
Extinguishing media:	Use foam, dry chemical, or water spray to extinguish fire.
Special firefighting procedures:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool fire exposed surfaces and to protect personnel.
Unusual fire & explosion hazards:	Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. Heavy flammable vapors may settle along ground level and low spots to create an invisible fire hazard. The vapors may extend to sources of ignition and flash back.
Byproducts of combustion:	Fumes, smoke, oxides of carbon and nitrogen.
Autoignition temperature:	Not determined.
Explosion data:	Not determined. Care should always be exercised in dust/mist conditions.
Other:	Not determined.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spill control procedures (land):	Eliminate sources of ignition. Prevent additional discharge of material, if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (Section 15) notify the National Response Center. Prevent liquid from entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust. Recover by explosion proof pump, hand pump, or suitable absorbent, into appropriate containers. Dispose of in accordance to local ordinances.
Spill control procedures (water):	Eliminate sources of ignition. Warn occupants and shipping in surrounding and downwind areas of fire and explosion hazard and request all to stay clear. Remove from surface by skimming or with suitable adsorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in non-confined waters. Recover adsorbed material into suitable containers and dispose of in accord with local disposal codes.
Waste disposal method:	Material may be incinerated at licensed incineration sites - check with local waste companies. All disposals must comply with federal, state and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.
Other:	CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.

SECTION 7 HANDLING AND STORAGE

Handling procedures:	Keep containers closed when not in use. Do not transfer to unmarked containers. Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106 -- Flammable and Combustible Liquids. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Polaris Material Safety Data Sheet

Storage procedures: Store containers such that they are protected from weather elements (rain, snow, direct sunlight). Containers may absorb water through container closures if stored improperly. Store containers away from heat, sparks, open flame, or oxidizing materials.

Additional information: No additional information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection: Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.

Respiratory protection: None required if airborne concentrations are maintained below threshold limits listed on page one. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.

Eye protection: Eye protection is recommended. If material is handled such that it could be splashed into the eyes, wear safety glasses with side shields or vented/splash proof goggles (ANSI Z87.1 or approved equivalent).

Hand protection: Impervious gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption.

Other protection: Use of an apron and overboots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization and absorption. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated.

Local control measures: Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored.

Other: Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or smoking.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Vapor pressure: Not determined.

API gravity: 36.3 at 15.6°C (60.0°F).

Density: 7.02 lbs/gal at 15.6°C (60.0°F).

Specific gravity: 0.84 at 15.6°C (60.0°F).

Solubility: Negligible in water, soluble in most petroleum solvents.

Percent volatile: Not determined.

Vapor density (air=1): Greater than air.

Evaporation rate (n-Butyl Acetate=1): Not determined.

Odor: Mild petroleum

Appearance: Clear fluid with orange tint

Viscosity: 5.3 cSt at 100°C (212°F).

Boiling point: Not determined.

Pour point: -40°C (-40°F).

Other: Not applicable.

Polaris Material Safety Data Sheet

SECTION 10

STABILITY AND REACTIVITY

Stability:	Stable.
Conditions to avoid:	Avoid high temperatures and product contamination.
Incompatibility with other materials:	Avoid contact with acids and oxidizing materials such as liquid chlorine or concentrated oxygen.
Decomposition products:	Smoke, carbon monoxide and dioxide, and other aldehydes of incomplete combustion. Oxides of carbon and nitrogen.
Hazardous polymerization:	Will not occur.
Other:	Not determined.

SECTION 11

TOXICOLOGICAL INFORMATION

Oral toxicity:	Not determined.
Dermal toxicity:	Not determined.
Inhalation toxicity:	On rare occasions, prolonged and repeated exposure to oil or solvent mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptotic as a result of repeated small aspirations. Shortness of breath and cough are the most common symptoms. Based on data from similar materials.
Dermal sensitization:	Prolonged or repeated contact may make skin more sensitive to other skin sensitizers. Based on data from similar materials.
Chronic toxicity:	Not determined.
Carcinogenicity:	Not determined.
Mutagenicity:	Not determined.
Reproductive toxicity:	Not determined.
Other:	Not applicable.

SECTION 12

ECOLOGICAL INFORMATION

Environmental toxicity:	This material has not been evaluated for its environmental impact. This material may be toxic to aquatic organisms and should be kept out of sewage and drainage systems and all bodies of water. Based on data from similar materials.
Environmental fate:	This product has not been evaluated for its environmental fate.
Other:	Not determined.

SECTION 13

DISPOSAL CONSIDERATIONS

Waste disposal:	Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. This product unadulterated by other materials may be classified as a non-regulated waste in some areas - but still needs to be disposed of at approved facilities. Waste management should be in full compliance with federal, state, and local laws.
Disposal consideration:	Most used oil and solvent is reclaimed or incinerated (if unadulterated). Place used, contaminated, or excess material into disposable containers and dispose of in a manner consistent with local and state regulations. Contact local environmental or health authorities for approved disposal of this material.
Other:	If material is contaminated with a regulated material, the whole of the material becomes a regulated waste. Try to segregate from regulated material waste streams.

Polaris Material Safety Data Sheet

provided by those materials manufacturers or distributors.

Version: I

INFORMATION PROVIDED IN THIS MSDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF POLARIS'S KNOWLEDGE. HOWEVER, POLARIS MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. POLARIS ASSUMES NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions: Section 14, updated transportation information. 01/25/2010
MSDS reviewed 8/4/2010